
RF PIC EVALUATION WITH RFCONNECT





AT A GLANCE

A compact RF PIC assembly for fast and convenient prototype development up to 40 GHz.

Features

- 8 RF I/O ports
- 8 optical I/O ports
- 42 DC I/O ports
- Therm. controllable
- Lid cover available


Applications

- controlling PICs for telecom applications, signal processing, signal generation and more
- enabling fast prototype development
- replacing expensive lab equipment
- overcoming manual electrical probing and optical coupling
- standardizing measurements


Technical Background

RFconnect, Fraunhofer HHI's fiber coupled RF PIC assembly, states a compatible expansion of the already established DC multisource PIConnect. The thermally controllable assembly with 8 RF & optical ports and 42 DC ports facilitates the connection of RF measurement equipment.





RFconnect Evaluation Board with clamped module including the PIC



Packaged PIC with RF, DC and fiber coupling (left), RFconnect PIC design template (right)



Expansion Board to connect HHI's DC multisource PIConnect Mainboard

M. Sc. Axel Schönau Photonic Components

Phone +49 30 31002-494 axel.schoenau@hhi.fraunhofer.de

Fraunhofer Heinrich Hertz Institute Einsteinufer 37, 10587 Berlin Germany

www.hhi.fraunhofer.de/pc