

CONTINUOUS WAVE TERAHERTZ EMITTER MODULES



AT A GLANCE

Photomixing terahertz emitters for 1.5 μm optical wavelength, emitted THz power confirmed by PTB (Physikalisch Technische Bundesanstalt)



Features

- Up to 800 μW THz power
- Up to 5.5 THz bandwidth
- Photodiode-based emitter
- Robust housing and fiber coupling


Applications

- High-bandwidth terahertz spectroscopy
- Industrial process control
- Non-contact coating film thickness measurement
- High-speed measurements
- High-speed wireless communication

Technical background

The photoconductive generation of continuous wave (cw) terahertz radiation converts the beat frequency of two lasers into an electrical THz signal. The frequency resolution of cw THz systems is only limited by the linewidth of the lasers. Preferred applications for continuous wave THz radiation are high resolution spectroscopy and imaging as well as precise monitoring of particular spectral lines.

HHI's THz modules utilize mature telecom technology and thus allow benefiting from THz technologies within industrial applications and environments.



Performance of cw THz emitter modules in a coherent spectrometer for operation conditions given in the specifications [Deumer et al., JIMT 45 (2024)].

Specifications

- Optical wavelength: 1.5 μm
- Optical power: 30 mW
- Bias voltage: -1.5 V
- Spectral range: 0.1 - 5.5 THz
- Output power:
 - >680 μW @ 100 GHz
 - >12 μW @ 500 GHz
 - >1 μW @ 1 THz
- Diameter of module: 25 mm



Dr. rer. nat. Robert Kohlhaas
 Hybrid Integration and Sensing

Phone +49 30 31002-407
 robert.kohlhaas@hhi.fraunhofer.de

Fraunhofer Heinrich Hertz Institute
 Einsteinufer 37, 10587 Berlin
 Germany

www.hhi.fraunhofer.de/pc

Deumer, M., Nellen, S., Lauck, S. et al. Ultra-Wideband PIN-PD THz Emitter with >5.5 THz Bandwidth. *J Infrared Milli Terahz Waves* 45, 831–840 (2024).